

GME® 2AEX SHIELD

GME® 2AEX SHIELDS

The GME® 2AEX Shield is an aluminum extruded shield with a slim, 2" wall that comes standard with a tough, T-6 knife edge and rugged top cap. Massive, extruded end members ensure strength. Available in lengths to 12-feet, it is sized for rubber-tired backhoes, and priced competitively.

OPTIONS

- Standard square-box tubing struts
- End loading struts
- 5" Schedule 80 pipe
- Screw-jack type struts
- Lifting eyes and bridle
- Pullbar
- No-knife edge
- Certified by a registered professional engineer to meet OSHA standards



**Standard Features Include
Knife Edge and Top Cap!**

GME® 2AEX SHIELD

2AEX – 2" ALUMINUM EXTRUDED WALL								
MODEL	SIZE			WEIGHT (LBS)	MAXIMUM DEPTH PER SOIL TYPE (FT.)			
	H	L	W		A	B	C-60	C-80
2AEX-66	6'	6'	2"	724	67	38	29	21
2AEX-68	6'	8'	2"	906	37	21	17	12
2AEX-610	6'	10'	2"	1088	23	14	11	8
2AEX-612	6'	12'	2"	1270	15	9	8	5
2AEX-86	8'	6'	2"	943	45	26	20	14
2AEX-88	8'	8'	2"	1177	34	20	15	11
2AEX-810	8'	10'	2"	1412	23	14	11	8
2AEX-812	8'	12'	2"	1647	15	9	8	5

NOTE: 2AEX Boxes come standard with knife edge and protective top cap. Optional "no knife edge" panels are available.

GME's 2AEX gives you the choice of several spreader options. This allows you to pick the one that best suits your needs.

STANDARD SPREADERS (For use when working 2 sided)

SPREADER SETS <small>Pinned in place adjustable, box steel tube, 3.5" x 3.5"</small>		
MODEL	RANGE	WT. (LBS.)
2AEX-AB	Adapt. Brckts (8/set)	64
2AEX-2640	26-40"	112
2AEX-3250	32-50"	136
2AEX-3859	38-59"	164
2AEX-4468	44-68"	188
2AEX-5692	56-92"	248

END LOADABLE STRUTS (Allows you to work 2, 3, or 4 sided by end loading your box for repair work)

END LOADABLE STRUTS <small>3.5" x 7.5" steel tube</small>		
MODEL	RANGE	WT. (LBS.)
2AEX-SS-AB	Adapt. Brckts (8/set)	80
2AEX-SS-2640	26-40"	216
2AEX-SS-3250	32-50"	264
2AEX-SS-3859	38-59"	312
2AEX-SS-4468	44-68"	368
2AEX-SS-5692	56-92"	456

LITE-SHIELD™ STRUTS (Screw jack type spreaders)

LITE-SHIELD STRUTS		
MODEL	RANGE	WT. (LBS.)
LSS-AB	Adapter Brackets (8/set)	64
24LSS-1	24-32"	48
24LSS-2	32-48"	64
24LSS-2.5	40-64"	84
24LSS-3	51-86"	100

*We also offer the option of standard steel spreaders – 5" Schedule 80 Pipe

OPTIONAL ACCESSORIES

2AEX PULLBARS		
MODEL	RANGE	WEIGHT (LBS.)
2AEX-PB-40	26"-40"	26
2AEX-PB-50	32"-50"	32
2AEX-PB-59	38"-59"	41
2AEX-PB-68	44"-68"	54
2AEX-PB-92	56"-92"	62

NOTE: Pullbars come with built-in Lift Eyes (2). Extra 1/2 set Lift Eyes are required with Pull Bar.

2AEX LIFT & STACK ACCESSORIES	
MODEL	WEIGHT (LBS.)
2AEX2 Lift Eye pair (2)	12
2AEX-LE Lift Eye set (4)	24
Nylon sling – 6-ft.	7
Nylon sling – 8-ft.	9
2AEX Stacking pins w/Bolts (4)	20

ICM of America
Internet Sales
877-494-5793