

*OPTIONAL CUT-OUTS AVAILABLE

24" x 24" 36" x 36"

Manhole Shields

MH SERIES MANHOLE SHIELDS: with spreaders and attaching hardware										
MODEL	SIZE			PIPE	WEIGHT	SHIELD CAP.	MAXIMUM DEPTH PER SOIL TYPE (FT.)*			
	Н	W	L	CLEARANCE	(LBS)	(PSF) (LBS)	Α	В	C-60	C-80
MH SERIES SINGLEWALL (STEEL)										
MH8SW	8'	8'	8'	45"	3565	689	32	19	15	13
MH10SW	8'	10'	10'	45"	4085	448	22	14	11	10
MH48SW	4'	8'	8'	N/A	2348	908	38	22	17	13
MH410SW	4'	10'	10'	N/A	2732	590	26	15	12	9
MH SERIES DOUBLEWALL (STEEL)										
MH8DW	8'	8'	8'	45"	4104	1764	75	43	33	26
MH10DW	8'	10'	10'	45"	4787	1147	50	29	23	18
MH12DW	8'	12'	12'	45"	6244	805	36	22	17	14
MH48DW	4'	8'	8'	N/A	2803	2221	91	51	39	30
MH410DW	4'	10'	10'	N/A	3316	1444	60	34	26	20
MH SERIES DOUBLEWALL (STEEL) WITH CUT-OUTS										
MH410DW	8'	8'	8'	45"	4387	1924	81	47	36	28
MH410DW	8'	10'	10'	45"	5084	1252	54	32	25	20
MH410DW	8'	12'	12'	45"	5781	879	39	24	19	15

Our MH Series made of high tensile steel, are heavier and are rated for deeper jobs. The square manhole configuration surr ounds the pit and provides the needed inside clearspan while reducing the amount of excavation and r estoration required. They assemble in minutes at the jobsite. Standard models include two walls, two spreader assemblies, eight holding pins and keepers. All are certified by a professional engineer to meet OSHA standards.

ICM of America Internet Sales 877-494-5793