

**SCHONSTEDT**   
INSTRUMENT COMPANY  
*Making Locating Easier Since 1953*

**Go  
ahead.**

**Make  
your  
move.**

**SCHONSTEDT  
GA-92** 



# The most portable magnetic locator ever made.



Detect the magnetic fields of all ferromagnetic objects—property markers, manholes, septic tanks, well casings, valve boxes, cast iron pipes, steel drums, unexploded ordnance—up to sixteen feet below the surface.



*Extends for greater sensitivity*



*Retracts for easier carrying*



**Two models to choose from**

**XT<sup>d</sup> MODEL**  
 LCD gain, battery and signal strength/polarity display

**XT<sup>i</sup> MODEL**  
 with LCD gain and battery display

## Model GA-92XT<sup>i</sup> and GA-92XT<sup>d</sup> Specifications

<b>Output</b>	<b>Audio:</b> Signal increases in frequency with gradient field intensity. Idle frequency = 10 Hz. <b>Visual:</b> Expanding bar-graphs indicate polarity (positive or negative) and relative signal strength (GA-92XT <sup>d</sup> model only)
<b>Battery Indicator</b>	4-segment LCD
<b>Gain</b>	Continuous control, with range indicated by a 4-segment LCD at each quarter turn, L @ 0-1/4, M @ 1/4-1/2, H @ 1/2-3/4, XH @ 3/4-Full
<b>Volume</b>	Continuous control
<b>Input Power</b>	Supplied by one 9 V battery (Lithium recommended, but not required)
<b>Battery Life</b>	24 Hours (intermittent usage)
<b>Operating Temperature</b>	-13 Degrees F to 140 Degrees F (25 Degrees C to 60 Degrees C)
<b>Water Resistant Length</b>	11.5 in (~29 cm) (when extended)
<b>Overall Length</b>	<b>Unit extended:</b> 26 in (~66 cm) <b>Unit collapsed:</b> 15.5 in (~39 cm)
<b>Nominal Sensor Spacing</b>	9.5 in (~24 cm)
<b>Weight</b>	Approximately 2.4 Lbs (1.1 Kg)
<b>Construction</b>	13% glass-filled, high impact ABS, .2" (~5 mm) wall thickness



*Rugged carrying case included*



*Headphones optional (or use your own)*

*Holster included!*

ICM of America  
 Internet Sales

800-877-4571 Ext. 2010