

SPECIALTY ANCHORAGE CONNECTORS

These specialty anchors combine ease-of-use and strength to provide fall protection safety to match the task. They all have been rigorously tested to meet or exceed industry standards.

MOBI-LOK™ SELF CONTAINED VACUUM ANCHOR SYSTEMS

Provides a tie-off point on virtually any smooth, non-porous surface simply by flipping a switch and waiting for the green light.

- Fall arrest tested and approved, meeting OSHA, CE and AS/NZS
- Lightweight design (under 20 lbs.) for easy transport
- Fail-safe back-up systems with audio alarms and vacuum level indicator
- Rubber seals secure anchor without damaging surface
- Can be used with horizontal lifeline systems for added mobility for two workers

2200095

MOBI-LOK™ FOR GENERAL INDUSTRY

Self-contained vacuum anchor assembly with bottle attachment and carrying case. It is powered up with a single, on-board 48-cubic-inch compressed gas bottle (order separately) or a large capacity detached bottle, or shop air. Unit can also power one additional secondary pad.

2200094 Mobi-Lok™ general industry self contained vacuum anchor without bottle attachment

2200096 Mobi-Lok™ general industry self contained vacuum anchor secondary pad

2200108

MOBI-LOK™ FOR AVIATION INDUSTRY

Self-contained vacuum anchor assembly with bottle attachment and carrying case. It is powered up with a single, on-board 48-cubic-inch compressed gas bottle (order separately) or a large capacity detached bottle, or shop air. Unit can also power one additional secondary pad.

- EPDM rubber seals are Skydrol resistant.
- Aviation rated electronics are intrinsically safe.

2200107 Mobi-Lok™ aviation industry self-contained vacuum anchor without bottle attachment

2200109 Mobi-Lok™ aviation industry self-contained vacuum anchor secondary pad

Mobi-Lok™ 4-man 100 ft. (30 m) and 150 ft. (45 m) systems also available featuring twin horizontal lifeline systems.



2200094



2200108

MOBI-LOK™ ACCESSORIES

2200078

Compressed gas cylinder



2200086

Fill station, fills compressed gas cylinder 2200078 from bulk nitrogen cylinder.



2200130

Secondary pad hose x 50 ft. (15 m). For connecting secondary pads to self-contained vacuum anchor.



1225013

FORCE2™ shock absorbing lanyard with web loop choker at one end, aluminum carabiner at other x 6 ft. (1.8 m).



2200400

Sayflite™ horizontal lifeline system x 40 ft. (12 m). For connection between two or more pads to create continuous protection for two workers.





SAFLOK™ WOOD POLE AND STEEL STRUCTURE ANCHOR SYSTEMS

2104801

Provides wood pole climber with 100% fall protection, allowing installation of anchor and lifeline to top of pole from the ground. Quickly and safely climb prior to connecting work positioning system.

- Compatible with most hot stick poles
- Includes anchor tube with installation/removal tool
- 80 ft. (24 m) 5/8" (16 mm) dielectric rope and two carabiners
- Rope grab with shock absorbing lanyard
- Chain tensioner, web loop and carrying bag



2104810 Saflok™ Steel Structure Fall Arrest System with anchor tube, installation/removal tool, 80 ft. (24 m) 5/8" (16 mm) high dielectric rope, carabiner, rope grab with shock absorbing lanyard, rescue loop sling and carrying bag.

FIRST-MAN-UP™ REMOTE ANCHORING SYSTEM



2104527

Provides a safe means to anchor a fall protection device to an overhead location beyond normal reach.

- Pole adjusts from 6 to 12 ft. (1.8 to 3.6 m)
- Tie-off adapter tool for installation of anchorage device
- Hook attachment tool for installation of 3,600 lb. gated snap hooks
- Tie-off adapter x 3 ft. (0.9 m) and carrying bag

2104528 First-Man-Up™ System with 8-16 ft. (2.4-4.8 m) adjustable pole

2104529 Snap hook connector tool for 3,600 lb. gated hooks

2104530 First-Man-Up™ System, 6-12 ft. (1.8-3.6 m) adjustable pole with original and 3,600 lb. gated hook tools

2104531 First-Man-Up™ System, 8-16 ft. (2.4-4.8 m) adjustable pole with original and 3,600 lb. gated hook tools



2100090

PERIMETER LIMITER LEADING EDGE ANCHOR

Freestanding, non-penetrating anchor is ideal for concrete decking construction and provides overhead anchorages for up to 2 users.

- Large foam filled trailer tires won't go flat and will provide easy movement
- Rotating 7.5 ft. (2.3 m) mast and anchorage arm for added freedom of movement
- Pre-drilled holes for accessory rescue winches or jobsite boxes
- Additional weights and taller mast can be added for jobsite flexibility

2100091 9-1/2 ft. mast for perimeter limiter



2100080

DOOR/WINDOW JAMB ANCHOR

Non-penetrating anchor is lightweight and portable, requiring no tools for attachment. Adjustable opening ranging from 21.5" to 51.5" (54.6 cm to 130.8 cm). Rated for 3,600 lbs. (16kN).

