

## STEEL ANCHORAGE CONNECTORS

Extremely versatile anchors for steel are lightweight and compact, providing an easy to install and safe 5,000 lb. (22kN) tie-off point for your personal fall protection system.



### 2104700

#### GLYDER™ 2 SLIDING BEAM ANCHOR

Provides complete horizontal mobility on I-beams, attach overhead or at your feet (use with Force2™ shock absorbing lanyard when used at your feet).

- Wear pads eliminate metal-to-metal contact, for smooth operation
- Integrated ratcheting adjustment system for easy installation
- Dual beam grip adjustment prevents twisting and turning
- Extremely lightweight at only 3.7 lbs. (1.66 kg)
- User capacity of 420 lbs. (189 kg)
- Fits flange 3-1/2" to 14" wide and up to 1-1/4" thick



### 2110941

#### GLYDER™ SLIDING BEAM ANCHOR

The original Glyder™ has most of the features of Glyder™ 2, except the adjustment system is detent pin type and fits larger beam sizes. Fits flange 6"-18" wide and up to 2-1/2" thick.



### 2108406

#### FIXED BEAM ANCHOR

It installs in seconds to the beam structure in any orientation, with final tightening using a built-in adjustment handle. Ideal as a single-person anchor point or as end-anchors for a Sayflite™ horizontal lifeline system. Fits up to 1-1/2" thick beam flange, 2-1/2" to 12" wide.

**2108407** Fixed Beam Anchor, fits up to 1-1/2" thick x 2-1/2"-18" wide beam flange

**2108408** Fixed Beam Anchor, fits up to 1-1/2" thick x 2-1/2"-24" wide beam flange

**2108410** Fixed Beam Anchor, fits up to 1/2" to 2-1/2" thick x 12"-36" wide beam flange

## 2103143

### TROLLEY FOR I-BEAM

The trolley is for use with self retracting lifelines on horizontal beams and has been engineered for ease-of-use and superior performance. Glides effortlessly along the beam and provides horizontal mobility.

- Attachable anywhere along beam, including midpoint
- Non-corrosive double-shielded wheel bearings are maintenance free
- Trolley Guards protect the wheels from damage and keep beam clear of debris
- Fits 3" to 8" flange width thickness up to 11/16"

**2103147** Trolley for I-Beam, all stainless steel, fits 3" to 8" flange width thickness up to 11/16"

## 2101630

### D-RING ANCHORAGE PLATE

The D-ring anchorage plate can be bolted or welded to a structure, offering a compact, reliable connection point for your fall protection system.

- Two 1/2" diameter attachment holes
- Cadmium plated steel D-ring
- 304 stainless steel anchorage plate
- Plate size: 1/4" x 2" x 4-1/2"

**2101634** D-ring Anchorage Plate with cadmium plated steel D-ring, raw steel anchorage plate

**2101636** D-ring Anchorage Plate with 304 stainless steel D-ring and anchorage plate

**2101638** D-ring Anchorage Plate with 316 stainless steel D-ring and anchorage plate

## 2104550

### STEEL PLATE ANCHOR

This plate anchor offers a compact, reliable attachment to 3/8" to 1" thick plate steel for connecting your lanyard, vertical lifeline system or self retracting lifeline.

- Easy to use set-screw design ensures positive and safe connection
- Complete with integral D-ring tie-off point
- Durable, corrosion resistant zinc plated steel construction

