

CONFINED SPACE RESCUE

ADVANCED TRIPODS

Advanced Tripods are constructed of lightweight tubular aluminum with a rugged steel head assembly. The UCT series tripods can be combined with up to three pulleys to accommodate a variety of winches and fall arrest devices to meet a wide range of confined space entry/retrieval and rescue requirements. Quick release pins positively locate components at all adjustment points for tool-less set-up and adjustment.



■ TOP MOUNTED PULLEY SYSTEM

Mount up to three pulleys to route mechanical device lifelines for smooth operation.

■ SECONDARY ANCHOR POINT

5,000 lb. (22 kN) anchor point for secondary fall arrest system on 7 ft. models—11,000 lb. (49kN) rating on 10 ft. models.

■ ALUMINUM CONSTRUCTION

Extremely lightweight yet durable construction for ease-of-use and longevity.

■ TELESCOPING LEGS

Provide fast adjustment and cannot disengage, for added worker satisfaction.

■ ADJUSTABLE HEIGHT LEGS

Fast and easy detent pin style adjustment allows for precise height setting.

■ QUICK CONNECT BRACKET

Allows fast and easy attachment of mechanical devices.

■ SAFETY CHAIN

Provides added support and strength for demanding confined space applications.

■ INNER LEG LINERS

Allow for smooth positive connection and operation of leg adjustment.

■ FOOT PADS

Include sharp points for biting into soft ground and/or uneven terrain.

■ MECHANICAL DEVICES

Can support up to 3 winches or SRLs for complete flexibility.

8513159

ADVANCED UCT-1000 10' (3.05 m) TRIPOD

With adjustable locking legs, safety chains, top pulley and winch bracket.

Weight: 68 lbs. (30.8 kg)

Note: Winch not included—please order separately.



8513158

ADVANCED UCT-300 7' (2.13 m) TRIPOD

- Lightweight, durable aluminum construction with powder coat finish
- Includes quick connect winch mount bracket—can accommodate up to three brackets
- Includes top mounted pulley system—can accommodate up to three pulleys
- Telescoping adjustable locking legs for easy set-up
- Fast detent pin style adjustment and locking
- Inner plastic liners provide smooth adjustment
- Foot pads include sharp points for biting into soft ground and/or uneven terrain
- Safety chain for added support, strength and safety
- 5,000 lb. (22 kN) built-in head-mounted anchor point

Winch and SRL not included—please order separately.



8000000

ADVANCED 7' (2.13 m) ALUMINUM TRIPOD

- Lightweight, durable aluminum construction
- Includes quick connect winch mount bracket
- Includes top mounted pulley system
- Telescoping adjustable locking legs for easy set-up
- Fast detent pin style adjustment and locking
- Rubber safety shoes with spiked edges for different terrains
- Safety chain for added support, strength and safety
- 5,000 lb. (22 kN) built-in head-mounted anchor points

Winch not included—please order separately.

8000010 9 FT. (2.7 M) ALUMINUM TRIPOD

With adjustable locking legs, safety chains, top pulley and winch bracket.

Winch not included—please order separately.

ADVANCED ACCESSORIES



8513329 Carrying bag for 7' (2.1 m) 8513158 tripod with protective plastic liner

8513330 Carrying bag for 10' (3 m) 8513159 tripod with protective plastic liner

9503094 Carrying bag for 7' (2.1 m) 8000000 tripod

9503095 Carrying bag for 9' (2.7 m) 8000010 tripod



8512292

WINCH/SRL MOUNTING BRACKET FOR 8513159 TRIPOD

Attaches to the leg tube with quick-release pins for tool-less set-up and adjustment.

Weight: 5.2 lbs. (2.4 kg)



8510224

WINCH/SRL MOUNTING BRACKET FOR 8513158 TRIPOD

Attaches to the leg tube with quick-release pins for tool-less set-up and adjustment.

Weight: 3 lbs. (1.4 kg)

NOTE: Also see accessories on page 140 for additional bracket options.



8512293

TOP PULLEY ASSEMBLY FOR UCT SERIES TRIPODS

Pulleys are mounted on top of the head assembly to route mechanical device's lifeline over and into confined space area.

Weight: 1.6 lbs. (.73 kg)