

ICM of America  
Internet Sales  
877-494-5793



Husqvarna®



## Husqvarna K 3600 MK II

The Husqvarna K 3600 MK II is a cutter with performance and features that make it unique. The eccentric drive of the blade means the cutting depth is a huge 10". Its unique power / weight ratio and hydraulic drive make for a highly efficient and maneuverable handheld cutter. It is well suited to a wide range of applications, including both brick and reinforced concrete. The combination of large cutting depth and high capacity without set-up time make the K 3600 MK II one of the most productive tools in the business.



## Features Husqvarna K 3600 MK II

- Hydraulic gear motor
- Peripheral drive
- Adjustable front handle
- Automatic start for water flow
- 10" cutting depth with 14" blade, thanks to unique eccentric drive.
- Stable support rollers for easier adjustment and blade change.
- Sealed drive and roller system.
- Adjustable front handle with integrated, convenient water adjustment.
- Large lower spray guard and integrated support foot.
- Low weight and ergonomic design.
- Supplied with grease gun, to simplify greasing of the guide rollers.
- Simple service and cleaning.

### TECHNICAL SPECIFICATION

Power output	5.8 hp
Hydraulic flow, max	10 gal/min
Hydraulic pressure	140 bar
Max cutting depth	10 inch
Blade diameter	14 inch
Weight (excl. cutting equipment)	18.3 lbs
Vibrations front handle	4.3 m/s <sup>2</sup>
Vibrations rear handle	6 m/s <sup>2</sup>
Sound power level, guaranteed (LWA)	111 dB(A)
Sound pressure level at operators ear	99 dB(A)

