ICM of America Internet Sales 877-494-5793






GBC — Cart Type

The ideal combination of GloBug, generator, and heavy duty cart — GBC Series

- Steerable cart design for easy transportation sets up without tools; easy to maneuver.
- **Metal Halide lamp** single 1,000 watt lamp for maximum illumination. Pure white light — 3400° K.
- 360° glarefree illumination with standard balloon.
- Quick restrike time 3 to 5 minutes.
- Universally adaptable to all AC power supplies accepts 50/60Hz, 100-240V.
- **Downward direct illumination** with reflector balloon.
- **Self-inflating balloons** are easy to install and inflate in less than 20 seconds.
- Three-stage mast extends up to 12' 1".
- **Three outriggers** for great stabilization.
- System can be broken down and placed in the trunk of a car.
- Light coverage up to 150 feet.

Illumination Range



Footcandles	Feet	
	BAL115D	
10	27	
5	36	
2	57	
1	82	
0.5	110	
0.25	168	

Specifications			
Model	GBC	GBCE	
Voltage (V)	100-240V		
Amps (A)	9.3 @ 120V		
Hz	50-60		
Minimum Wattage Req.	1,200 Watts		
Plug Type	5 - 15P		
Lamp Type	1,000 watt Metal Halide (x1)		
Total Luminous Flux (Im)	110,000		
Standard Balloon Diameter in. (mm)	47.2 (1200)		
Outriggers	3		
Mast — Number of stages	3 Stages (Air Shock Absorbers)	4 Stages (Air Shock Absorbers)	
Upper Position Working Dimensions LxWxH in. (mm)	51.2x52.2x94.5 to 145.7 (1,300 x 1,325 x 2,400 to 3,700)	51.2x52.2x94.5 to 180.7 (1,300 x 1,325 x 2,400 to 4,590)	
Storage Dimensions LxWxH in. (mm)	27.6 x 40 x 47.7 (700 x 1,023 x 1,212)		
Balloon Dimensions LxWxH in. (mm)	47.2 x 47.2 x 28.3 (1200 x 1200 x 720)		
Weight lb. (kg)	127 (57.2)	130.7 (59.3)	

