

ICM of America Internet Sales 877-494-5793

Series SLBU & SLHPBU 3,000 PSI with Blue Slither® Cover

All Piranha® Slither® sewer hoses are constructed with a yellow polyolefin tube, high tensile synthetic braid reinforcement to reach the desired pressure rating and then covered with a high abrasion resistant slick polyether-urethane cover.


Identification of Piranha® Hose Products is simple. The inner tube of all Piranha® Sewer Cleaning Hose is yellow as assigned by WASTEC. To assure proper matching of all components, the hose tube material, end fittings, menders and tooling are color coded yellow.

Hose Temperature Range -

For the diameters of 1/2", 3/4" and 1" is -40°F (-40°C) to +150°F (+66°C).

SLBU & SLHPBU Hoses

Standard high pressure hoses are available in 3 ID sizes; Piranha® SLBU & SLHPBU Hoses are built to provide rugged and reliable service for sewer cleaning applications.



Results 1 - 3 of 3

Item #	Size Code	Nominal I.D. Size	Nominal O.D.	Max. Operating Pressure	Min. Burst Pressure	Min. Bend Radius	Weight
SLHPBU-12	12	0.75 in 19.1 mm	1.18 in 30.0 mm	3000 PSI 206.80 bar	7500 PSI 517.10 bar	5 in	0.29 lbs/ft
SLHPBU-16	16	1 in 25.4 mm	1.48 in 37.6 mm	3000 PSI 206.80 bar	7500 PSI 517.10 bar	8 in	0.41 lbs/ft
SLBU-08	08	.50 in 12.8 mm	0.83 in 21.2 mm	3000 PSI 206.80 bar	7500 PSI 517.10 bar	4 in	0.16 lbs/ft

Results 1 - 3 of 3