

ICM of America  
Internet Sales  
877-494-5793

**Series SPOR Orange Cover 2,500 PSI Hose Assemblies**

All Piranha® sewer hoses are constructed with a yellow polyolefin tube, high tensile synthetic braid reinforcement to reach the desired pressure rating, and then covered with a high abrasion resistant polyether-urethane cover.


Identification of Piranha® Hose Products is simple. The inner tube of all Piranha® Sewer Cleaning Hose is yellow as assigned by WASTEC. To assure proper matching of all components, the hose tube material, end fittings, menders and tooling are color coded yellow.

**Hose Temperature Range -**

For the diameters of 3/4", 1" and 1 1/4" is -40°F (-40°C) to +150°F (+66°C).

**SPOR Hose Assemblies**

Standard high pressure hoses are available in 3 ID sizes. Piranha® SPOR hose assemblies are built to provide rugged and reliable service for sewer cleaning applications.



Results 1 - 8 of 8

Item #	Size Code	Hose I.D.	Male NPTF Nom. Thread Size	Max. Working Pressure	Assembled Length	Weight (per Package)
SPOR-MM12X400	12	0.75 in	3/4 - 14	2500 PSI	400 ft	112.0 lbs
SPOR-MM12X500	12	0.75 in	3/4 - 14	2500 PSI	500 ft	140.0 lbs
SPOR-MM12X600	12	0.75 in	3/4 - 14	2500 PSI	600 ft	168.0 lbs
SPOR-MM16X400	16	1 in	1 - 11 1/2	2500 PSI	400 ft	160.0 lbs
SPOR-MM16X500	16	1 in	1 - 11 1/2	2500 PSI	500 ft	200.0 lbs
SPOR-MM16X600	16	1 in	1 - 11 1/2	2500 PSI	600 ft	240.0 lbs
SPOR-MM16X800	16	1 in	1 - 11 1/2	2500 PSI	800 ft	320.0 lbs
SPOR-MM20X600	20	1.25 in	1 1/4 - 11 1/2	2500 PSI	600 ft	354.0 lbs

Results 1 - 8 of 8