

HydraPaks

Gasoline HydraPaks

RGC HydraPaks are powerful, portable hydraulic power supplies that operate more efficiently and with less noise than other types of power systems. Choose from a variety of models with Briggs & Stratton, Honda and Subaru engines. Many HydraPaks have variable flow and pressure settings making them ideal for powering RGC tools, as well as other compatible hydraulic tools.

Features and Benefits

- Compact, lightweight hydraulic power source for RGC and other compatible hydraulic tools.
- Cart-mounted with large 16 in. pneumatic tires for easy transporting.
- Low noise level. Much quieter than an air compressor.
- Easy maintenance and parts replacement.
- Electric start and low oil shutdown on all models.
- Controls easily accessible for safety and comfort.
- Powder-coated tubular steel frame protects unit from damage.
- Lifting eye and detachable handles for easy transporting and storage.
- 6 gallon oil reservoir and heavy duty 8-tube heat exchanger on most models.
- Extra heavy duty 10-tube heat exchanger, full set of gauges and a 6 gallon removable gas tank on the HH2010, HV2310 and HV2312.



HV2312 HydraPak



HV1810 Control Panel w/ Gauges

Gas HydraPak Specifications

Model	Engine	Fuel Capacity	Pressure (maximum)	Flow	Hourmeter	Weight (approximate)
HH1358	Honda 13 hp	7 qt. (6.6 ltr)	2250 psi (155 bar)	5 - 8 gpm (20 or 30 lpm)	Yes	226 lbs. (103 kg)
HR1458	Subaru 14 hp	7 qt. (6.6 ltr)	2250 psi (155 bar)	5 - 8 gpm (20 or 30 lpm)	Yes	226 lbs. (103 kg)
HV1658	B&S 16 hp Vanguard V-Twin	9 qt. (8.6 ltr)	2250 psi (155 bar)	5 - 8 gpm (20 or 30 lpm)	Yes	226 lbs. (103 kg)
HV1858	B&S 18 hp Vanguard V-Twin	9 qt. (8.6 ltr)	2250 psi (155 bar)	5 - 8 gpm (20 or 30 lpm)	Yes	240 lbs. (109 kg)
HV1810	B&S 18 hp Vanguard V-Twin	10 qt. (8.6 ltr)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	0 - 10 gpm (0 - 38 lpm)	Yes	249 lbs. (113 kg)
HV1810XL	B&S 18 hp Vanguard V-Twin	11 qt. (8.6 ltr)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	0 - 10 gpm (0 - 38 lpm)	Yes	260 lbs. (116 kg)
HH2010	Honda 20 hp	6 gal (22.7 ltr)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	0 - 10 gpm (0 - 38 lpm)	Yes	285 lbs. (129 kg)
HV2310	B&S 23 hp Vanguard V-Twin	6 gal (22.7 ltr)	2000 psi (138 bar) 2500 psi (172 bar) 3400 psi (231 bar)	0 - 10 gpm (0 - 38 lpm)	Yes	280 lbs. (127 kg)
HV2312	B&S 23 hp Vanguard V-Twin	6 gal (22.7 ltr)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	0 - 12 gpm (0 - 45 lpm)	Yes	280 lbs. (127 kg)

HydraPaks

HydraPaks

RGC HydraPaks are powerful, portable hydraulic power supplies that operate more efficiently and with less noise than other types of power systems. Choose from a variety of models including electric, bi-directional and dual-output. Many HydraPaks have variable flow and pressure settings making them ideal for powering RGC tools, as well as other compatible hydraulic tools.

Electric HydraPaks have the advantage of being ideal for indoor work. Equipped with a 10 hp or 15 hp electric motor they are the contractors' choice for jobs in hospitals, schools, municipal buildings and other public facilities.

Bi-Directional HydraPaks are designed for installing anchoring systems and similar jobs.

Dual-Output HydraPaks can power either one tool or two tools requiring 5 gpm simultaneously.

Dual-Output HydraPak Specifications

Model	HV1855	HV185510
Engine	B&S 18 hp Vanguard V-Twin	B&S 18 hp Vanguard V-Twin
Fuel Capacity	9 qt. (8.6 ltr)	9 qt. (8.6 ltr)
Flow	Run 2 tools @ 5 gpm (20 lpm)	Run 2 tools @ 5 gpm (20 lpm) or 1 tool @ 10 gpm (38 lpm)
Pressure (max.)	2250 psi (155 bar)	2250 psi (155 bar)
Hourmeter	Yes	Yes
Weight (approx.)	251 lbs (114 kg)	251 lbs (114 kg)



HV1855 Dual-Output HydraPak

HydraPak Features and Benefits

- Compact, lightweight hydraulic power source for RGC and other hydraulic tools.
- Cart-mounted with large 16 in. pneumatic tires for easy transporting.
- Low noise level. Much quieter than an air compressor.
- Easy maintenance and parts replacement.
- Controls easily accessible for safety and comfort.
- Powder-coated tubular steel frame protects unit from damage.
- Lifting eye and detachable handles for easy transporting and storage.
- 6 gallon oil reservoir and heat exchanger.

Electric HydraPak Specifications

Model	HE1058	HE1010	HE1512
Engine	10 hp Electric Motor	10 hp Electric Motor	15 hp Electric Motor
Flow	5 or 8 gpm (20 or 30 lpm)	0 - 10 gpm (0 - 38 lpm)	0 - 12 gpm (0 - 45 lpm)
Pressure (max.)	2250 psi (155 bar)	1750 psi (120 bar) 2000 psi (138 bar) 2500 psi (172 bar)	1750 psi (120 bar) * 2000 psi (138 bar) * 2500 psi (172 bar)**
Hourmeter	Yes	Yes	Yes
Weight (approx.)	221 lbs (100 kg)	260 lbs (118 kg)	280 lbs (127 kg)

*Continuous duty cycle. **Intermittent duty only.

Bi-Directional HydraPak Specifications

Model	HH1358C	HV1658C	HV1858C
Engine	Honda 13 hp	B&S 16 hp Vanguard	B&S 18 hp Vanguard V-Twin
Fuel Capacity	7 qt. (6.5 ltr)	9 qt. (8.5 ltr)	9 qt. (8.5 ltr)
Flow	5 or 8 gpm (20 or 30 lpm)	5 or 8 gpm (20 or 30 lpm)	6 or 8 gpm (20 or 30 lpm)
Pressure (max.)	2250 psi (155 bar)	2250 psi (155 bar)	2251 psi (155 bar)
Hourmeter	Yes	Yes	Yes
Weight (approx.)	228 lbs (103 kg)	228 lbs (103 kg)	249 lbs (113 kg)



HV1858 Bi-Directional HydraPak



HE1010 Electric HydraPak