

PLUG TECHNOLOGIES PLUGS SOLD BY ICM OF AMERICA

Multi-Size FatBoy Guzzlers™

Our Multi-Sized Guzzler™ Plugs can be used for blocking flow, air testing (testing and blocking), vacuum testing and bypassing flow, making the Guzzlers™ our most versatile multisize plugs.

Natural rubber construction gives our Guzzler™ plugs a broad usage range.

Polyester cord gives our plugs strength and durability.

The lightweight aluminum bypasses make our Guzzler™ plugs lightweight and easy to install.

Optional Max-Guard™ on 15"-30" and larger plugs. The Max-Guard™ relief valve helps prevent the plug from being over inflated due to user error or malfunctioning gauges.



Recommended Applications:

bypassing flow, gravity bypassing, air testing (testing and blocking), vacuum testing.

Size Usage Range

Description	Part #	Minimum Diameter	Maximum Diameter	Maximum Allowable Back Pressure PSI and Head	Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolts Size & Quantity	Bypass Size (s)
3"-4" FatBoy Guzzler™	250-34	2.75" 75mm	4.3" 109mm	20 PSI	35 PSI	.75 LBS	2.65"	6.25"	1/8" Tank Valve (removable)	(1) 1/4"	1/4" NPT (F)
4" - 6" FatBoy Guzzler™	250-46	3.75" 100mm	6.4" 162mm	17 PSI	45 PSI	2.25 lbs	3.5"	9"	1/8" Tank Valve (removable)	(1) 1/4"	3/4" NPT (F)
6"-10" FatBoy Guzzler™	250-610	5.5" 150mm	10.5" 250mm	13 PSI	30 PSI	7 lbs	5.25"	17.5"	1/8" Tank Valve (removable)	(1) 1/4"	2" NPT (F)
8"-12" FatBoy Guzzler™	250-812	7" 200mm	12.64" 321mm	13 PSI	25 PSI	11.5 lbs	6.75"	19"	1/4" Tank Valve (removable)	(1) 3/8"	3" NPT (F)
12"-18" FatBoy Guzzler™ with 4" Bypass	274-1218	10.75" 300mm	18.5" 450mm	10 PSI	35 PSI	47 lbs	10.5"	32"	1/4" Tank Valve (removable)	3/16" x 7/8" Galvanized Shackles	4" (M) NPT
15"-30" FatBoy Guzzler™ with 4" Bypass	250-1530	14" 375 mm	30.5" 750mm	11 PSI	25 Psi	68 lbs	13.75"	58"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts	4" (M) NPT
15"-30" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve)	250-1530MG	14" 375 mm	30.5" 750mm	11 PSI	25 Psi	68 lbs	13.75"	58"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts	4" (M) NPT
15"-30" FatBoy Guzzler™ with 4" Bypass and Max-Sleeve™ Installed	250-1530MS	14" 375 mm	30.5" 750mm	11 PSI	25 Psi	90 lbs	13.75"	58"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts	4" (M) NPT
15"-30" FatBoy Guzzler™ with 4" Bypass and Max-Guard™ (Relief Valve) and Max-Sleeve™ Installed	250-1530MGMS	14" 375 mm	30.5" 750mm	11 PSI	25 Psi	90 lbs	13.75"	58"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts	4" (M) NPT