

PLUG TECHNOLOGIES PLUGS SOLD BY ICM OF AMERICA

Multi-Size FatBoy Plugster™

Our durable Multisize FatBoy Plugster™ works in any pipe that falls inside the plug's size usage range.

Our Multisize Plugsters™ are ideal for rental customers because each plug will cover several different pipe sizes which allows better utilization of the asset.

The Multisize Plugster™ style plugs are designed specifically for either blocking flow or holding air/vacuum pressure.

Our Multisize Plugsters™ are the most economical multi-size plugs and are great for contractors or municipalities that are working with different diameter pipes but do not need air testing capabilities.

Our Multisize Plugsters™ natural rubber constructions allow our FatBoy Plugs™ to be flexible enough to bend at a 90 degree angle making them very easy to install.

Removable/replaceable 1/4" tank valve (tire valve) are standard on all Fatboy Plugsters™.

Optional Max-Guard™ on 15"-30" plugs and larger protects the plug from being over inflated due to operator error or malfunctioning gauges.

Innovative manufacturing process allows our 15"-30" and larger plugs to be vulcanized in one cure. This process also allows us use high strength cording throughout the plug and around each end of the plug to ensure maximum strength and durability.

Recommended Applications: Plugsters™ are designed for blocking flow or holding back air pressure. They have no bypass so they can't be used for bypassing flow or used on the front side (test side) of an air test.

Recommended Optional Accessories:

Fill Kits/Retrieval Rope with gauge



Pictured: 200-1530MG



PLUG TECHNOLOGIES PLUGS SOLD BY ICM OF AMERICA

Multi-Size FatBoy Plugster™

Description	Part #	Size Usage Range		Maximum Allowable		Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolts Size & Quantity
		Minimum Diameter	Maximum Diameter	Back Pressure PSI and Head							
3-4" FatBoy Plugster™	200-34	3" 75mm	4.3" 109mm	20 PSI		35 PSI	0.66 LBS	2.75"	6"	1/8" Tank Valve Removable	1/4" (1)
4" - 6" FatBoy Plugster™	200-46	4" 100mm	6.4" 162mm	17 PSI		45 PSI	1.5 LBS	3.5"	9"	1/8" Tank Valve Removable	1/4" (1)
6"-10" FatBoy Plugster™	200-610	6" 150mm	10.58" 268mm	13 PSI		30 PSI	4.5 LBS	5"	17.25"	1/4" Tank Valve Removable	3/8" (1) & (1) Optional 3/8" Backside Eyebolt
8"-12" FatBoy Plugster™	200-812	8" 200mm	12.64" 321mm	13 PSI		25 PSI	6.75 LBS	6.75"	19"	1/4" Tank Valve Removable	3/8" (1) & (1) Optional 3/8" Backside Eyebolt
12"-18" FatBoy Plugster™	200-1218	12" 300mm	18.50" 479mm	13 PSI		25 PSI	24 Lbs	10.75"	28"	1/4" Tank Valve Removable	3/8" (2) & (1) Optional 3/8" Backside Eyebolt
12"-24" FatBoy Plugster™	200-1224	12" 300mm	24.5" 600mm	13 PSI		30 PSI	27 lbs	10.75"	37"	1/4" Tank Valve Removable	3/8" (2) & (1) Optional 3/8" Backside Eyebolt
15"-30" FatBoy Plugster™	200-1530	14" 375 mm	30.5" 750mm	11 PSI		25 Psi	50 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Guard™ (Relief Valve)	200-1530MG	14" 375 mm	30.5" 750mm	11 PSI		25 Psi	50 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Sleeve™ Installed	200-1530MS	14" 375 mm	30.5" 750mm	11 PSI		25 Psi	71 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside
15"-30" FatBoy Plugster™ With Max-Guard™ (Relief valve) and Max-Sleeve™ Installed	200-1530 MGMS	14" 375 mm	30.5" 750mm	11 PSI		25 Psi	71 lbs	13.75"	50"	(1) 1/4" Tank Valve (removable) (1) 1/2" (F) NTP Port	(2) 1/2" Eyebolts (2) 1/2" Optional Backside



Optional Accessories:

Max-Sleeves™ Available for plugs sizes 12"-18" and larger.

Fill Kits /Retrieval Rope with Gauge



ICM OF AMERICA INTERNET SALES 877-494-5793

