

# PLUG TECHNOLOGIES PLUGS SOLD BY ICM OF AMERICA

## Multi-Size FatBoy Rapid Placement Plugs™ RPP

Our **FatBoy Rapid Placement Plugs (RPP)™** plugs are designed to allow the user to quickly and easily install a plug without getting into the manhole.

**No need for confined space entry equipment** and procedures saving the user a significant amount of time.

**Easy pull pin makes adjusting the angle** of the plug during installation very rapid. Six different pin placements gives six different angle options.

**Removable/replaceable 1/4" tank valve** (tire valve) standard on all Fatboy RPP™ plugs.

**Light weight easy snap together poles** make lifting and lowering the RPP™ plugs into and out of different depth manholes quick and easy. For deeper manholes just snap together more 6' poles.

**Recommended Applications:** Air Testing (blocking side) Blocking Flow, Vacuum Testing.



Description	Part #	Size Usage Range		Maximum Allowable Back Pressure PSI and Head	Required Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Eye Bolts Size & Quantity
		Minimum Diameter	Maximum Diameter							
6"-10" FatBoy RPP™	215-610	6" 150mm	10.58" 268mm	13 PSI 30 Ft	30 PSI	6 LBS	5"	17.25"	1/4" Tank Valve Removable	3/8" (1) & (1) Optional 3/8" Backside Eyebolt
8"-12" FatBoy RPP™	215-812	8" 200mm	12.64" 321mm	13 PSI 30 Ft	25 PSI	8 Lbs	6.75"	19"	1/4" Tank Valve Removable	3/8" (1) & (1) Optional 3/8" Backside Eyebolt
RPP Adapter Aluminum	65-079									
RPP Pole 6' Aluminum	31-215									

## FatBoy Max-sleeve™

Our FatBoy Max-sleeves™ were designed to be an extra protective layer (1/4" natural rubber) over our 12"-18" multisize FatBoy™ plugs and all larger size plug products greatly reduces damage a plug can sustain from pipeline debris, degraded pipe and sharp objects. **Protect your plug to the Max!**

Description	Part #	Product Weight	Product Length	Eyelets
12"-18" Oversleeve	600-1218	10 lbs	28 "	(4) 3/8" on each end
12"-24" Oversleeve	600-1224	13.25 lbs	39"	(4) 3/8" on each end
15"-30" Oversleeve	600-1530	21 Lbs	50.5"	(4) 3/8" on each end

