

PLUG TECHNOLOGIES PLUGS SOLD BY ICM OF AMERICA

Single Size FatBoy Guzzler™

Our natural rubber single size inflatable Guzzler™ plugs are used in a variety of different applications including blocking flow, bypassing and air testing.

Guzzlers™ are the most versatile and economical inflatable bypass plugs.

Aluminum bypasses make these plugs lightweight and easy to install.

Our plugs come standard with a removable 1/8" or 1/4" tank valve (tire valve).

Our 3" plastic molded two port (1/2" and 1/4") Guzzler™ plug makes it easy to convert our Guzzlers™ into Testers™ without purchasing any additional conversion caps/plugs.

Our plugs also include a removable eyebolt (1/4" or 3/8") for lifting and lowering the plug.



Recommended Accessories:


Part # 410-30

30' Fill Kit without gauge (Swivel-Ball)



Recommended

Applications: blocking flow, air testing, bypassing pumping flow and gravity bypassing.



Size Usage Range				Maximum Allowable	Required					Eye Bolts	
Description	Part #	Minimum Diameter	Maximum Diameter	Back Pressure PSI and Head	Inflation Pressure	Weight	Deflated Diameter	Deflated Length	Inflation Fitting	Size & Quantity	Bypass Size (s)
6" FatBoy Guzzler™	150-06	5.25" 127mm	6.4" 162mm	15 PSI 34 Ft	35 PSI	3 Lbs	4.75"	6"	1/8" Tank Valve (Removable)	(1) 1/4"	1.5" NPT (F)
8" FatBoy Guzzler™	150-08	7 " 171mm	8.55" 217mm	15 PSI 34 Ft	35 PSI	6.5 Lbs	6.75"	8"	1/4" Tank Valve (Removable)	(1) 3/8"	3" NPT (F)
10" FatBoy Guzzler™	150-10	9" 222mm	10.58" 268mm	15 PSI 34 Ft	35 PSI	10 Lbs	8.75"	10"	1/4" Tank Valve (Removable)	(1) 3/8"	3" NPT (F)
12" FatBoy Guzzler™	150-12	11" 273mm	12.64" 321mm	15 PSI 34 Ft	35 PSI	14.75 Lbs	10.75"	12"	1/4" Tank Valve (Removable)	(1) 3/8"	3" NPT (F)
3" Molded 2 Port Bypass Conversion Plug	50-100										

ICM OF AMERICA INTERNET SALES 877-494-5793



2