PLUG TECHNOLOGIES SOLD BY ICM OF AMERICA

Tru-TestTM Max-FillTM/Retrieval Rope 3/8" ID Hose with Gauge

Our combination retrieval rope (used to lift and lower plugs into and out of the manhole) and inflation line (used to inflate and deflate your plugs) is our Max-Fill heavy duty offering. The large 3/8" ID hose allows you to inflate and deflate your plug 40% faster than our standard 1/4" hose. The gauge tree includes a removable 0-60 PSI liquid filled gauge with snubber, a tank valve (Tire Valve) and a 1/4" quick dump valve. The removable gauge featured in the 440 series allows you to quickly remove the gauge for safe storage and transporting.


Heavy Duty natural rubber Gauge Guardian™ protects your gauge from the hazardous construction environment.

The retrieval rope has a 3,000 lbs tensile strength which protects the fittings on the fill kit from being tugged on while the plug is lifted into and out of a manhole.



440 Series includes a removable gauge

440 Series



Description	Part #	Product Weight	Product Length
20' Tru-Test Max-Fill Kit/Retrival Rope with Removable Liquid Filled Gauge	440-20	8 Lbs	20' 6.09 m
30' Tru-Test Max-Fill Kit/Retrival Rope with Removable Liquid Filled Gauge	440-30	10 Lbs	30' 9.15 m
40' Tru-Test Max-Fill Kit/Retrival Rope with Removable Liquid Filled Gauge	440-40	12 Lbs	40' 12.2 m
20' Tru-Test Max-Fill Kit/Retrival Rope with Gauge	435-20	8 Lbs	20' 6.09 m
30' Tru-Test Max-Fill Kit/Retrival Rope with Gauge	435-30	10 Lbs	30' 9.15 m
40' Tru-Test Max-Fill Kit/Retrival Rope with Gauge	435-40	12 Lbs	40' 12.2 m

PLUG TECHNOLOGIES SOLD BY ICM OF AMERICA

Tru-Test^m Fill Kit/Retrieval Rope 1/4²² ID Hose With and Without Gauge Options

This combination retrieval rope and inflation hose can be used to lift and lower plugs into and out of the manhole and has a fill line for inflating and deflating plugs from outside of the danger zone.

The polypropylene rope has a 3,000 lbs tensile strength which protects the fill line from being tugged on during the installation of your plugs.

The snap hook makes it easy to attach and detach the retrieval rope from the plug. The fill line comes with a tank valve (tire valve) on one side and either an industrial quick disconnect or a swivel ball (tire valve) connection on the other side.

The 430 Series includes a gauge tree consisting of a 0-60 PSI liquid filled gauge with snubber, a tank valve (tire valve) and a 1/4" quick dump valve.



Includes Gauge Tree





410 Series

420 Series

20' Tru-Test Standard-Fill Kit/Retrival Rope without Gauge with Swivel Ball Fittings	410-20	4 Lbs	20' 6.09 m
30' Tru-Test Standard-Fill Kit/Retrival Rope without Gauge with Swivel Ball Fittings	410-30	5.5 Lbs	30' 9.15 m
40' Tru-Test Standard-Fill Kit/Retrival Rope without Gauge with Swivel Ball Fittings	410-40	7 Lbs	40' 12.2 m
20' Tru-Test Standard-Fill Kit/Retrival Rope without Gauge with QD Fitting	420-20	4 Lbs	20' 6.09 m
30' Tru-Test Standard-Fill Kit/Retrival Rope without Gauge with QD Fitting	420-30	5.5 Lbs	30' 9.15 m
40' Tru-Test Standard-Fill Kit/Retrival Rope without Gauge with QD Fitting	420-40	7 Lbs	40' 12.2 m
20' Tru-Test Standard-Fill Kit/Retrival Rope with Gauge	430-20	5 Lbs	20' 6.09 m
30' Tru-Test Standard-Fill Kit/Retrival Rope with Gauge	430-30	7 Lbs	30' 9.15 m