

The Vutek 2017 system has fully-loaded features to assist users with sewer inspections. The user-friendly keypad has been redesigned with an easy "On Demand" recording and snapshot button to help speed up inspection time. Technicians can easily record vital inspection data and client information using the available on-screen text-writer and footage counter. Built with a 1.3" modular, self-leveling camera head that is geared to inspect sewer pipes from 3" up to 12" inch diameter and a built-in sonde which broadcasts a 512 Hz frequency which is locatable with a 512 Hz locator.

ICM INTERNET SALES 877-494-5793




NEW MOBILE PHONE APP




Download Insight Vision App to an Android™ or Apple™ phone.

Wi-Fi Video Streaming App





One-Touch Recording and Snapshot





Keypad and On-Screen Text Enable

Type in vital information to display and record on video.



Built-in Microphone and Speaker

Record voiceover video and play it back.



On-Screen Footage Counter

View the distance pushed and display on screen.



Built-in 512 Hz Frequency Sonde

Broadcast a 512hz signal to be locatable with a 512hz locator.



Included External Battery Power Back

Power up the system for up to 6 hours on a full charge.



QUICK CHANGE MODULAR CAMERA

- 1.3" Diameter Camera Head
- **Quick Camera Head Repair**
- Clear Resolution Video
- **Clearview Gorilla Glass**
- **Durable Stainless Steel Body**
- **Self-Leveling Camera Head**





















REEL COVER 2" SKID

3" SKID

USB STICK

POWER PACK

SUN SHADE CAR POWER CORD

ICM INTERNET SAL 877-494-5793

CONTROL SYSTEM



SPECIFICATIONS Case Dimensions: 12"L x 10"W x 9"H

Video Resolution: 640 x 480

Data Storage: 8GB USB stick * Included with the system

Keyboard: Full "QWERTY" style membrane

Recording format: H.264 Image Capture: JPG Text Generator: Yes

Distance Counter: Displays on screen FT/M

Video Out: Yes Camera Test Port: Yes

One Touch Recording Controls:

Power Source: 12V 5Amp DC * Included with the system

8.4" LCD Size: Weight: 13 lbs.

Battery: External Lithium-ion * Included with the system

CAMERA HEAD



Self-Leveling:

2" L x 1.3" Diameter Dimensions:

640 x 480 Camera Resolution: Weight: 5.9 Ounces Light Ring: 12 LED Imager Sensitivity: .025 Lux Image Size/ Type: 1/4" CMOS

Construction: Stainless Steel Body LED Window: Polycarbonate Camera Window: Gorilla Glass

PUSH ROD/ FRAME



200-300-400ft, Available, Cable Length:

Pipe Size: 3" to 12"

Cable Jacket: Polypropylene jacket

Cable core: Spiral Wound Fiberglass push rod

Push Rod Dia.: 0.475" OD

30"L x 16-1/2"W x 32-1/2"H Dimensions:

Weight: 62 lbs. (200 ft.) Sonde Frequency: 512Hz

Protective Skids: 2" & 3" * Included with the system

MOBILE PHONE APP



Local Wi-Fi: Operating System:

Controls: File transfer: Video Connection:

Image Format:

Stream Wireless Video (No Internet Needed)

Android & ISO devices capable (Free Download) View, record, playback and snapshot

Upload to Email or YouTube Video Stream Up to 100ft.

JPG