PRIMUS

USB-USA

5005

5013 | 5010

5020

PRIMUS I

P/N	Hose Con.	Minimum/GPM	Pipe Diameter	L x W Dimensions	Weight	Rear Jets	Front Jets	Radial Jets	Tier
5005	½"	12	4" - 8"	4.33" x 2.36"	2,64	3	1	4	3

PRIMUS II

P/N	Hose Con.	Minimum/GPM	Pipe Diameter	L x W Dimensions	Weight	Rear Jets	Front Jets	Radial Jets	Tier
5010	¾"	30	6" - 10"	5.90" x 4.72"	7,05	4	1	4	3
5013	1"	60	6" - 15"	6.29" x 4.72"	8,37	5	1	4	3

PRIMUS III

P/N	Hose Con.	Minimum/GPM	Pipe Diameter	L x W Dimensions	Weight	Rear Jets	Front Jets	Radial Jets	Tier
5020	1¼"	80	12" - 24"	1.18" x 5.90"	20,94	6	1	4	3

Capable of controlled rotation and being used with recycled water, the Primus is very innovative and effective. The nozzle is built from hardened stainless steel and is extremely user friendly because it requires no lubrication or replacement of the internal parts for at least 1 year. A rotating head removes grease, light scale, and light roots combined with 3D fluid mechanics in the propulsion unit flush the debris out producing the best cleaning results!

ICM OF AMERICA

877-494-5793