

STANDARD NOZZLE



1256













1260



1255



1262

 P/N	 Hose Con.	 Minimum/GPM	 Pipe Diameter	 L x W Dimensions	 lbs.Weight	 Rear Jets	 Front Jets	 Radial Jets	 # Tier
1251	1 1/4"	80	8" - 12"	3.14" x 2.36"	2,2	10	1	----	2
1256	1"	50	6" - 12"	3.14" x 2.16"	1,76	10	1	----	2
1255	1"	50	6" - 12"	2.04" x 2.28"	1,5	12	4	----	2
1257	3/4"	30	6" - 8"	2.55" x 1.69"	0,88	8	1	----	2
1259	3/4"	30	6" - 8"	2.55" x 1.69"	0,88	6	1	----	2
1260	1/2"	12	4" - 6"	1.18" x 1.96"	0,22	6	1	----	1
1262	1/2"	12	2" - 6"	1.06" x 1.25"	0,22	6	1	----	2
1268	3/8"	8	2" - 4"	1.37" x 0.98"	<0,22	6	1	----	1
1273	1/4"	3	up to 4"	0.78" x 0.78"	<0,22	6	1	----	1
1274	1/4"	3	up to 4"	0.78" x 0.78"	<0,22	6	1	----	1

Compact, lightweight and inexpensive are three words that sum up the Standard nozzle. Made from hardened stainless steel with a rear spray angle of 20° makes this nozzle perfect for cleaning smaller pipes. A front jet for penetration is also available.

ICM OF AMERICA

877-494-5793