


# Lansas<sup>®</sup> PRODUCTS

## AR<sup>™</sup> & SSB<sup>™</sup> SINGLE-SIZE BLOCKING PLUGS

Developed to block flow in pipelines or for testing, Lansas AR<sup>™</sup> plugs, 1-1/4" thru 6" feature a zinc plated chain and ring. The entire range of these plugs through 24" have test pressure ratings of as much as 15 psi with air or water. Our SSB<sup>™</sup> Single Size Blocking plugs offered in 8," 10" and 12" sizes with a newly formulated blend of natural rubber along with the AR<sup>™</sup> plugs are the toughest and most dependable single-size plugs available. The SSB<sup>™</sup>, like the SST<sup>™</sup> comes with a removable 3/8" eye bolt and a removable 1/4" (M) NPT tire inflation valve.

### TYPICAL PIPE APPLICATION



## THE LONG AR<sup>™</sup>

is designed to be installed through a cleanout or floor drain and seal within the wye. With a pressure rating of 15 psi, these plugs are excellent for use when pressure testing with air or water. The Long AR<sup>™</sup> plug is supplied with a 36" extension hose and a removable zinc-plated chain and ring.

**Custom Designs  
Are Always<sup>™</sup> Available**

**WARNING**  
BLOCK PLUGS TO PREVENT MOVING!

IMPROVED CONSTRUCTIONMETHODS 877 - 494 - 5793

## SST<sup>™</sup> & MST<sup>™</sup> SINGLE & MULTI SIZE TEST PLUGS

The Lansas SST<sup>™</sup> and MST<sup>™</sup> (Single and Multi-Size Test Plug) are similar in function to our MW<sup>™</sup> plugs, but the SST<sup>™</sup> and MST<sup>™</sup> are built with a newly formulated natural rubber compound. These plugs are the most durable, versatile, and toughest single size plugs available today.



The SST<sup>™</sup> and MST<sup>™</sup> Plugs are designed with multi-function in mind. Available in single sizes 8" through 24" and multi-size 8"- 12". Each of these have a 3" female NPT aluminum by-pass. These plugs can be used to stop flow, for sewer by-passing, or for air testing. An air test conversion cap comes supplied with every SST<sup>™</sup> and MST<sup>™</sup> Plug.



### Patent # 4,083,384 MULTI-WORKER PLUG

The Lansas MW<sup>™</sup> Multi-worker plug is the most versatile and cost effective single-size pipe plug available. Our 4" to 24" MW's<sup>™</sup> are molded with "o-ring" sealing ribs and each plug is equipped with a replaceable by-pass pipe. Our 15" through 24" MW's<sup>™</sup> come with either a 4," 6," or 8" by-pass. For air or water testing, sewer by-pass or simply stopping the flow, the MW<sup>™</sup> offers the best value in single size plugs. Test Caps are available to set up the MW<sup>™</sup> Plug for an air test. A PVC cap is supplied with each plug with up to a 6" NPT by-pass.



Test Cap Packages 545-01 545-02  
Conversion Caps shown with  
optional air test fittings.



SST<sup>™</sup> Plug  
shown with our  
new Triple Test  
SMART HOSE,  
available in  
25' or 50'  
lengths.  
Part No. 472-25  
& 472-50





877-494-5793

AR™ & SSB™ SINGLE SIZE BLOCKING PLUGS

PART NUMBER	RANGE OF USE		REQUIRED INFLATION PRESSURE	MAXIMUM BACK/TEST PRESSURE	PRODUCT DIMENSIONS		
	MINIMUM PIPE DIAMETER	MAXIMUM PIPE DIAMETER			LENGTH	DEFLATED DIAMETER	WEIGHT
030-.7515	0.7"	1.75"	30 psi	15 psi	5.8"	0.6"	0.5 lbs.
030-02	1.8"	2.25"	30 psi	10 psi	6.0"	1.5"	0.8 lbs.
030-03	2.8"	3.25"	30 psi	15 psi	6.0"	2.6"	1.0 lbs.
030-34*	2.6"	4.25"	45 psi	15 psi	7.3"	2.5"	1.0 lbs.
030-04	3.5"	4.25"	30 psi	15 psi	6.0"	3.3"	1.2 lbs.
030-46*	3.5"	6.25"	45 psi	15 psi	11.0"	3.4"	1.6 lbs.
030-06	5.5"	6.25"	30 psi	15 psi	6.0"	4.8"	1.8 lbs.
030-68*	4.7"	8.25"	35 psi	15 psi	14.5"	4.5"	2.8 lbs.
035-08*	6.8"	8.25"	25 psi	15 psi	7.8"	6.7"	5 lbs.
035-10*	8.8"	10.25"	25 psi	15 psi	9.8"	8.6"	8 lbs.
035-12*	10.8"	12.25"	25 psi	15 psi	11.8"	10.4"	11 lbs.
030-15*	13.0"	16.25"	25 psi	15 psi	16.0"	12.8"	22 lbs.
030-18*	17.0"	18.25"	25 psi	15 psi	16.0"	16.0"	35 lbs.
030-21*	19.0"	21.25"	25 psi	15 psi	16.0"	18.5"	41 lbs.
030-24*	23.0"	24.25"	25 psi	15 psi	16.0"	22.0"	55 lbs.

\*Not equipped with with the zinc plated chain and ring. Sizes 6" - 24" have a removable inflation fitting and eye-bolt.

LONG AR™ "All-Rubber" GRIP RIB PLUG

PART NUMBER	RANGE OF USE		REQUIRED INFLATION PRESSURE	MAXIMUM BACK/TEST PRESSURE	PRODUCT DIMENSIONS		
	MINIMUM PIPE DIAMETER	MAXIMUM PIPE DIAMETER			LENGTH	DEFLATED DIAMETER	WEIGHT
031-02	1.7"	2.25"	30 psi	15 psi	17.5"	1.5"	0.5 lbs.
031-03	2.7"	3.25"	30 psi	15 psi	19.5"	2.2"	1.0 lbs.
031-04	3.5"	4.25"	30 psi	15 psi	23.0"	3.0"	2.0 lbs.
031-46	3.8"	6.25"	30 psi	15 psi	26.0"	3.6"	3.0 lbs.

SINGLE SIZE TEST PLUG (SST™)

PART NUMBER	RANGE OF USE		REQUIRED INFLATION PRESSURE	MAXIMUM BACK/TEST PRESSURE	BYPASS SIZE	PRODUCT DIMENSIONS		
	MINIMUM PIPE DIAMETER	MAXIMUM PIPE DIAMETER				LENGTH	DEFLATED DIAMETER	WEIGHT
025-08	6.8"	8.25"	35 psi	15 psi	3"	8.8"	6.7"	6 lbs.
025-10	8.8"	10.25"	35 psi	15 psi	3"	10.8"	8.6"	10 lbs.
025-12	10.8"	12.25"	35 psi	15 psi	3"	12.8"	10.4"	16 lbs.
025-15	13.0"	16.25"	25 psi	15 psi	3"	16.0"	12.8"	29 lbs.
025-18	17.0"	18.25"	25 psi	15 psi	3"	16.0"	16.0"	35 lbs.
025-21	19.0"	21.25"	25 psi	15 psi	3"	16.0"	18.5"	43 lbs.
025-24	23.0"	24.25"	25 psi	15 psi	3"	16.0"	22.0"	60 lbs.

MULTI-SIZE TEST PLUGS (MST™)

025-812	7.3"	12.25"	25 psi	15 psi	3"	15.0"	7.0"	14 lbs.
---------	------	--------	--------	--------	----	-------	------	---------

MW™ PLUG (MULTI-WORKER™)

PART NUMBER	RANGE OF USE		REQUIRED INFLATION PRESSURE	MAXIMUM BACK/TEST PRESSURE	BYPASS SIZE	PRODUCT DIMENSIONS		
	MINIMUM PIPE DIAMETER	MAXIMUM PIPE DIAMETER				LENGTH	DEFLATED DIAMETER	WEIGHT
020-1.5	1.4"	1.75"	60 psi	20 psi	1/8"	4.0"	1.3"	0.4 lbs.
020-02	1.6"	2.25"	60 psi	20 psi	1/4"	5.0"	1.5"	0.7 lbs.
020-03	2.5"	3.25"	50 psi	20 psi	3/4"	9.0"	2.4"	1.5 lbs.
020-34	2.6"	4.25"	45 psi	15 psi	3/4"	9.0"	2.4"	1.7 lbs.
020-04	3.7"	4.25"	25 psi	15 psi	1"	8.0"	3.5"	2.0 lbs.
020-46	3.5"	6.25"	45 psi	15 psi	1"	14.0"	3.5"	2.2 lbs.
020-06	5.0"	6.25"	25 psi	15 psi	2"	8.0"	4.5"	3.0 lbs.
020-68	4.7"	8.25"	35 psi	15 psi	2"	17.5"	4.5"	5.3 lbs.
020-15	13.0"	16.25"	25 psi	15 psi	4"	16.0"	12.8"	37 lbs.
021-15	13.0"	16.25"	25 psi	15 psi	6"	16.0"	12.8"	43 lbs.
022-15	13.0"	16.25"	25 psi	15 psi	8"	16.0"	12.8"	48 lbs.
020-18	17.0"	18.25"	25 psi	15 psi	4"	16.0"	16.0"	43 lbs.
021-18	17.0"	18.25"	25 psi	15 psi	6"	16.0"	16.0"	49 lbs.
022-18	17.0"	18.25"	25 psi	15 psi	8"	16.0"	16.0"	54 lbs.
020-21	19.0"	21.25"	25 psi	15 psi	4"	16.0"	18.5"	51 lbs.
021-21	19.0"	21.25"	25 psi	15 psi	6"	16.0"	18.5"	59 lbs.
022-21	19.0"	21.25"	25 psi	15 psi	8"	16.0"	18.5"	62 lbs.
020-24	23.0"	24.25"	25 psi	15 psi	4"	16.0"	22.0"	68 lbs.
021-24	23.0"	24.25"	25 psi	15 psi	6"	16.0"	22.0"	76 lbs.
022-24	23.0"	24.25"	25 psi	15 psi	8"	16.0"	22.0"	79 lbs.