

Proudly designed and  
manufactured in North America

# HATHORN M7

## INSPECTION CAMERA SYSTEM



### Features

- 7.4" Impact resistant screen
- Self-leveling camera heads standard
- Straight view camera heads available
- One touch USB recording and video pause
- Adjustable camera lighting
- Onscreen footage counter
- External 18V battery compatibility
- 512hz sonde control
- Available with Wi-Fi
- PipeSTREAM™ stream/record

Hathorn M7 systems come standard with a 7.4" shatter resistant LCD monitor and are compatible with 18V Milwaukee® batteries for ultimate portability and over 4 hours of runtime on a single charge. All M7s come equipped with 200ft. of premium cable and your choice of Hathorn DuraCAM™ camera heads, all with cool running super bright LED lights. Trusted by plumbers and contractors all over North America to deliver rugged dependability and portability. Designed and manufactured in North America, with a full one-year warranty. The M7 offers a municipal grade product aimed at plumbers and contractors with an industry leading feature set.



Wi-Fi  
Available



Record  
to USB Drive



Compatible with  
18V Milwaukee®  
or equivalent batteries



Industry  
leading  
warranty



Self-leveling  
camera  
heads



**HATHORN**®  
INSPECTION CAMERAS

IMPROVED CONSTRUCTION  
METHODS

877-494-5793

Proudly designed and  
manufactured in North America

# HATHORN M7

**INSPECTION  
CAMERA SYSTEM**

## Specifications

- DuraCAM™ self-leveling or straight view camera heads with HD picture quality and auto-iris technology
- 1.23" - 12 dimmable cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 dimmable cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 dimmable cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Optional Wi-Fi PipeSTREAM™ stream/record (App for Apple or Android)
- Powered by 18V Milwaukee® or compatible batteries or 12V AC/DC adapter
- Ingress Protection of Reel & Camera Head – IPx5 & 60PSI
- Dimensions - 84cm x 48cm x 41cm / 33" x 19" x 16"
- Weight - 20kg / 45lbs



Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Max. Pipe Well Lit
M7W-2168-SL/M7W-2168	1.68"	Available	200 ft.	1/2"	3"	12"
M7-2168-SL / M7-2168	1.68"	Available	200 ft.	1/2"	3"	12"
M7W-2143-SL / M7W-2143	1.43"	Available	200 ft.	1/2"	3"	10"
M7-2143-SL / M7-2143	1.43"	Available	200 ft.	1/2" or 0.400"	3"	10"
M7W-2123-SL / M7W-2123	1.23"	Available	200 ft.	3/8"	2"	6"
M7-2123-SL / M7-2123	1.23"	Available	200 ft.	3/8" or 0.400"	2"	6"

### Accessories

Catalog #	Description
10108/10140	Regular skid for 1.68"/1.43"
10137/10123	Regular skid for 1.23 self leveling / 1.23" straight view
10109	3" grooved skid for 1.68" cameras
10160	3" grooved skid for 1.43" self leveling cameras
10187	P-trap skid for 1.43" straight view cameras
10162/10161	Roller skid for up to 12" pipe (1.68" / 1.43")



**HATHORN®**  
**INSPECTION CAMERAS**

**IMPROVED CONSTRUCTION  
METHODS**

**877-494-5793**