

Proudly designed and
manufactured in North America

HATHORN DuraScope™

Wi-Fi CAMERA REELS



Features

- Wi-Fi PipeSTREAM™ stream/record
- Self-Leveling camera heads standard
- Straight View camera heads available
- On-screen footage counter
- 512hz sonde control and reset
- External 18V battery compatibility
- Industry leading HDPE premium cables
- Genuinely North American Made

Hathorn Wi-Fi DuraSCOPE™ reels are designed to work with Hathorn's free app, PipeSTREAM™, available for Apple and Android. Stream video inspections directly to your mobile device; record, screen shot, make voice commentary and share video inspections seamlessly. All of these municipal grade Wi-Fi reels are compatible with 18V Milwaukee® or equivalent batteries for the ultimate in portability. Each reel is fitted with your choice of Hathorn DuraCAM™ self-leveling or straight view camera heads, all equipped with super bright cool running LEDs, for optimal HD picture quality. Butt welded steel frame construction, stainless steel camera heads, your choice of cable size, and Hathorn's legendary reliability allow you to push further than ever before and remain in the field longer. Hathorn Wi-Fi DuraSCOPE™ camera reels are trusted by plumbers, contractors, home inspectors, petrochemical companies, and mining engineers to deliver a high definition, recordable video inspection every time the camera is used.



Compatible with
18V Milwaukee®
or equivalent batteries



Industry
leading
warranty



HATHORN®
INSPECTION CAMERAS

IMPROVED CONSTRUCTION
METHODS

877-494-5793

Proudly designed and
manufactured in North America

HATHORN DuraScope™

Wi-Fi CAMERA REELS

Mini Wi-Fi Reel

Mid Wi-Fi Reel

Large Wi-Fi Reel

Specifications

- Compatibility – Wi-Fi PipeSTREAM™ stream/record,
- Hathorn's free app for Apple or Android portable devices
- Powered by external Milwaukee® or compatible 18V batteries.
- Hathorn DuraCAM™ self-leveling or straight view camera heads with auto-iris technology
- 1.00" - 8 cool running LEDs - 8k LUX @ 6"
- 1.23" - 12 cool running LEDs - 12k LUX @ 6"
- 1.43" - 16 cool running LEDs - 16k LUX @ 6"
- 1.68" - 20 cool running LEDs - 20k LUX @ 6"
- Choice of premium push-rod with HDPE jacket
- Sonde - 512 Hz High-power
- Operating Temperature – -30C to 60C (-22F to 140F)
- Ingress Protection of Reel & Camera Head – IPx5 & 60PSI



Large Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
WLR-4168-SL / WLR-4168	1.68"	Available	400 ft.	1/2"	3"	65 lbs.	12"	33" x 29" x 16"
WLR-3168-SL / WLR-3168	1.68"	Available	300 ft.	1/2"	3"	55 lbs.	12"	33" x 29" x 16"
WLR-2168-SL / WLR-2168	1.68"	Available	200 ft.	1/2"	3"	45 lbs.	12"	33" x 29" x 16"
WLR-4143-SL / WLR-4143	1.43"	Available	400 ft.	1/2"	3"	65 lbs.	10"	33" x 29" x 16"
WLR-3143-SL / WLR-3143	1.43"	Available	300 ft.	1/2"	3"	55 lbs.	10"	33" x 29" x 16"
WLR-2143-SL / WLR-2143	1.43"	Available	200 ft.	1/2"	3"	45 lbs.	10"	33" x 29" x 16"

Mid Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
WMR-2168-SL / WMR-2168	1.68"	Available	200 ft.	1/2"	3"	42 lbs.	12"	29" x 18" x 15"
WMR-2143-SL / WMR-2143	1.43"	Available	200 ft.	.400"	3"	42 lbs.	10"	29" x 18" x 15"
WMR-2123-SL / WMR-2123	1.23"	Available	200 ft.	.400"	2"	42 lbs.	6"	29" x 18" x 15"

Mini Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
WMN-2135	1.35"	No	200 ft.	3/8"	1.5"	33 lbs.	6"	24" x 18" x 10"
WMN-2123-SL / WMN-2123	1.23"	Available	200 ft.	3/8"	2"	33 lbs.	6"	24" x 18" x 10"
WMN-2100	1"	No	200 ft.	3/8"	1.5"	33 lbs.	4"	24" x 18" x 10"

* Skids are always recommended to protect camera head. Roller skids are recommended options for pipes larger than 8". Find these accessories and spare parts on our website - www.hathorncorp.com



IMPROVED CONSTRUCTION
METHODS
877-494-5793